













Aluminum Bar Grating

Aluminum Grating Table of Spacings

Part No.	Spacing	Open Area*	
19-ADT-4 19-SG-4 19-SGI-4		78%	Bearing bars spaced at 1-3/16" on center and cross bars at 4" on center. The workhorse of industrial flooring popular for platforms, catwalks, mezzanines and stairways.
19-ADT-2 19-SG-2 19-SGI-2		73%	Bearing bars spaced at 1-3/16" on center and cross bars at 2" on center. Excellent for short spans and applications where additional lateral stability is desired.
15-ADT-4 15-SG-4 15-SGI-4		75%	Bearing bars spaced at 15/16" on center and cross bars at 4" on center. More than 26% stronger than similar "19" spaced gratings and provides additional flooring surface.
15-ADT-2 15-SG-2 15-SGI-2		69%	Bearing bars spaced at 15/16" on center and close spaced cross bars at 2" on center. Provides the advantage of closer spaced bearing bars and cross bars.
11-ADT-4 11-SG-4 11-SGI-4		68%	Due to NAAMM allowable material and manufacturing tolerances, Interstate Gratings offers IGtru™ with bearing bars spaced at 21/32" on center, with 3/16" thick bearing bars to ensure compliance with the spacing requirements of the Americans with Disabilities Act. For ADA installations, specify that the bearing bars span perpendicular to the normal flow of traffic.
11-ADT-2 11-SG-2 11-SGI-2		63%	
IGtru™ 11-ADT-4		66%	
IGtru™ 11-ADT-4		61%	
8-ADT-4 8-SG-4 8-SGI-4		58%	The bar spacings on 8-4 and 8-2 gratings comply with ADA spacing requirements. In addition to pedestrian applications, these products are popular for material handling platforms and mezzanines subject to continuous cart and dolly traffic.
8-ADT-2 8-SG-2 8-SGI-2		54%	
7-ADT-4 7-SG-4 7-SGI-4		53%	The bar spacings on 7-4 and 7-2 gratings comply with ADA spacing requirements and are popular for applications in the public way. When specified with 3/16" thick bearing bars, 7-4 and 7-2 gratings have a net 1/4" clear opening between the bearing bars and often reject intrusion by high-heeled shoes.
7-ADT-2 7-SG-2 7-SGI-2		49%	

* Percentage of open area is based upon 3/16" thick bearing bars and .275 cross bars. Contact Interstate Gratings if exact open area calculation is required for alternative bearing bar thicknesses or cross bar sizes.

How to Specify Aluminum Bar Grating

- Select type of grating
 - "ADT" for Aluminum Dovetail Pressure Locked Grating
 - "SG" for Swaged Rectangular Bar Grating
 - "SGI" for Swaged "I-Bar" Grating
- Select bar spacing from table above
- Select bearing bar size (consult load tables on pages 15-20 considering service loads and clear spans anticipated)
- Specify Plain or Serrated surface
- Specify banding or additional trim required
- Specify finish
 - Mill finish (no finish)
 - Anodized (clear, bronze, other)
 - Powder coating
 - Other
- Specify fasteners (if required) – see page 40