

# Stainless Steel Bar Grating

Use this table when evaluating spans and loads for the following types of stainless steel grating:

## 11-WS-4, 11-DTS-4, 11-DTS-2

IGtrū™ is manufactured to NAAMM standards and is fully ADA compliant with a minimum 3/16" bearing bar thickness

**IGtrū™**  
Load Table

| Bearing Bar Size | Approx. Weight psf * | Maximum Pedestrian Span** |   | Unsupported Span |       |       |       |       |       |       |       |  |   |   |
|------------------|----------------------|---------------------------|---|------------------|-------|-------|-------|-------|-------|-------|-------|--|---|---|
|                  |                      |                           |   | 2'-0             | 2'-6  | 3'-0  | 3'-6  | 4'-0  | 4'-6  | 5'-0  | 5'-6  | 6'-0   | 6'-6  |   |
| 3/4 x 3/16       | 8.9                  | 4'-4"                     | U | 1,023            | 655   | 455   | 334   | 256   | 202   | 164   | 135   | All loads and deflections are theoretical and based upon the gross sections of the bearing bars, using a fiber stress of 20,000 psi. |   |   |
|                  |                      |                           | D | 0.114            | 0.179 | 0.257 | 0.350 | 0.457 | 0.579 | 0.714 | 0.864 |  |   |   |
|                  |                      |                           | C | 1,023            | 818   | 682   | 584   | 511   | 455   | 409   | 372   |  |   |   |
|                  |                      |                           | D | 0.091            | 0.143 | 0.206 | 0.280 | 0.366 | 0.463 | 0.571 | 0.691 |  |   |   |
| 1 x 1/8          | 8.0                  | 4'-10"                    | U | 1,212            | 776   | 539   | 396   | 303   | 239   | 194   | 160   | 135  | The values are not intended to be absolute since the actual load capacity will be affected by the slight variations in mill and manufacturing tolerances. |   |
|                  |                      |                           | D | 0.086            | 0.134 | 0.193 | 0.263 | 0.343 | 0.434 | 0.536 | 0.648 | 0.771  |   |   |
|                  |                      |                           | C | 1,212            | 970   | 808   | 693   | 606   | 539   | 485   | 441   | 404  |   |   |
|                  |                      |                           | D | 0.069            | 0.107 | 0.154 | 0.210 | 0.274 | 0.347 | 0.429 | 0.519 | 0.617  |   |   |
| 1 x 3/16         | 11.7                 | 5'-4"                     | U | 1,818            | 1,164 | 808   | 594   | 455   | 359   | 291   | 240   | 202  | 172   | Grating for spans to the left of the heavy line have a deflection $\leq 1/4"$ for uniform loads of 100 psi. |
|                  |                      |                           | D | 0.086            | 0.134 | 0.193 | 0.263 | 0.343 | 0.434 | 0.536 | 0.648 | 0.771  | 0.905   |   |
|                  |                      |                           | C | 1,818            | 1,455 | 1,212 | 1,039 | 909   | 808   | 727   | 661   | 606  | 559   |   |
|                  |                      |                           | D | 0.069            | 0.107 | 0.154 | 0.210 | 0.274 | 0.347 | 0.429 | 0.519 | 0.617  | 0.724   |   |
| 1-1/4 x 1/8      | 9.9                  | 5'-9"                     | U | 1,894            | 1,212 | 842   | 618   | 473   | 374   | 303   | 250   | 210  | 179   | 155   |
|                  |                      |                           | D | 0.069            | 0.107 | 0.154 | 0.210 | 0.274 | 0.347 | 0.429 | 0.519 | 0.617  | 0.724   | U = Safe Uniform Load in pounds/sq. ft.   |
|                  |                      |                           | C | 1,894            | 1,515 | 1,263 | 1,082 | 947   | 842   | 758   | 689   | 631  | 583   | C = Concentrated Load in pounds/ft. of grating width  |
|                  |                      |                           | D | 0.055            | 0.086 | 0.123 | 0.168 | 0.219 | 0.278 | 0.343 | 0.415 | 0.494  | 0.579   | D = Deflection in inches  |
| 1-1/4 x 3/16     | 14.5                 | 6'-4"                     | U | 2,841            | 1,818 | 1,263 | 928   | 710   | 561   | 455   | 376   | 316  | 269   | 232   |
|                  |                      |                           | D | 0.069            | 0.107 | 0.154 | 0.210 | 0.274 | 0.347 | 0.429 | 0.519 | 0.617  | 0.724   | 0.840   |
|                  |                      |                           | C | 2,841            | 2,273 | 1,894 | 1,623 | 1,420 | 1,263 | 1,136 | 1,033 | 947  | 874   | 812   |
|                  |                      |                           | D | 0.055            | 0.086 | 0.123 | 0.168 | 0.219 | 0.278 | 0.343 | 0.415 | 0.494  | 0.579   | 0.672   |
| 1-1/2 x 1/8      | 11.7                 | 6'-7"                     | U | 2,727            | 1,745 | 1,212 | 891   | 682   | 539   | 436   | 361   | 303  | 258   | 223   |
|                  |                      |                           | D | 0.057            | 0.089 | 0.129 | 0.175 | 0.229 | 0.289 | 0.357 | 0.432 | 0.514  | 0.604   | 0.700   |
|                  |                      |                           | C | 2,727            | 2,182 | 1,818 | 1,558 | 1,364 | 1,212 | 1,091 | 992   | 909  | 839   | 779   |
|                  |                      |                           | D | 0.046            | 0.071 | 0.103 | 0.140 | 0.183 | 0.231 | 0.286 | 0.346 | 0.411  | 0.483   | 0.560   |
| 1-1/2 x 3/16     | 17.5                 | 7'-3"                     | U | 4,091            | 2,618 | 1,818 | 1,336 | 1,023 | 808   | 655   | 541   | 455  | 387   | 334   |
|                  |                      |                           | D | 0.057            | 0.089 | 0.129 | 0.175 | 0.229 | 0.289 | 0.357 | 0.432 | 0.514  | 0.604   | 0.700   |
|                  |                      |                           | C | 4,091            | 3,273 | 2,727 | 2,338 | 2,045 | 1,818 | 1,636 | 1,488 | 1,364  | 1,259   | 1,169   |
|                  |                      |                           | D | 0.046            | 0.071 | 0.103 | 0.140 | 0.183 | 0.231 | 0.286 | 0.346 | 0.411  | 0.483   | 0.560   |
| 1-3/4 x 1/8      | 13.8                 | 7'-5"                     | U | 3,712            | 2,376 | 1,650 | 1,212 | 928   | 733   | 594   | 491   | 412  | 351   | 303   |
|                  |                      |                           | D | 0.049            | 0.077 | 0.110 | 0.150 | 0.196 | 0.248 | 0.306 | 0.370 | 0.441  | 0.517   | 0.600   |
|                  |                      |                           | C | 3,712            | 2,970 | 2,475 | 2,121 | 1,856 | 1,650 | 1,485 | 1,350 | 1,237  | 1,142   | 1,061   |
|                  |                      |                           | D | 0.039            | 0.061 | 0.088 | 0.120 | 0.157 | 0.198 | 0.245 | 0.296 | 0.353  | 0.414   | 0.480   |
| 1-3/4 x 3/16     | 20.3                 | 8'-0"                     | U | 5,568            | 3,564 | 2,475 | 1,818 | 1,392 | 1,100 | 891   | 736   | 619  | 527   | 455   |
|                  |                      |                           | D | 0.049            | 0.077 | 0.110 | 0.150 | 0.196 | 0.248 | 0.306 | 0.370 | 0.441  | 0.517   | 0.600   |
|                  |                      |                           | C | 5,568            | 4,455 | 3,712 | 3,182 | 2,784 | 2,475 | 2,227 | 2,025 | 1,856  | 1,713   | 1,591   |
|                  |                      |                           | D | 0.039            | 0.061 | 0.088 | 0.120 | 0.157 | 0.198 | 0.245 | 0.296 | 0.353  | 0.414   | 0.480   |
| 2 x 1/8          | 15.6                 | 8'-2"                     | U | 4,848            | 3,103 | 2,155 | 1,583 | 1,212 | 958   | 776   | 641   | 539  | 459   | 396   |
|                  |                      |                           | D | 0.043            | 0.067 | 0.096 | 0.131 | 0.171 | 0.217 | 0.268 | 0.324 | 0.386  | 0.453   | 0.525   |
|                  |                      |                           | C | 4,848            | 3,879 | 3,232 | 2,771 | 2,424 | 2,155 | 1,939 | 1,763 | 1,616  | 1,492   | 1,385   |
|                  |                      |                           | D | 0.034            | 0.054 | 0.077 | 0.105 | 0.137 | 0.174 | 0.214 | 0.259 | 0.309  | 0.362   | 0.420   |
| 2 x 3/16         | 23.1                 | 9'-0"                     | U | 7,273            | 4,655 | 3,232 | 2,375 | 1,818 | 1,437 | 1,164 | 962   | 808  | 689   | 594   |
|                  |                      |                           | D | 0.043            | 0.067 | 0.096 | 0.131 | 0.171 | 0.217 | 0.268 | 0.324 | 0.386  | 0.453   | 0.525   |
|                  |                      |                           | C | 7,273            | 5,818 | 4,848 | 4,156 | 3,636 | 3,232 | 2,909 | 2,645 | 2,424  | 2,238   | 2,078   |
|                  |                      |                           | D | 0.034            | 0.054 | 0.077 | 0.105 | 0.137 | 0.174 | 0.214 | 0.259 | 0.309  | 0.362   | 0.420   |
| 2-1/4 x 3/16     | 25.8                 | 9'-10"                    | U | 9,205            | 5,891 | 4,091 | 3,006 | 2,301 | 1,818 | 1,473 | 1,217 | 1,023  | 871   | 751   |
|                  |                      |                           | D | 0.038            | 0.060 | 0.086 | 0.117 | 0.152 | 0.193 | 0.238 | 0.288 | 0.343  | 0.402   | 0.467   |
|                  |                      |                           | C | 9,205            | 7,364 | 6,136 | 5,260 | 4,602 | 4,091 | 3,682 | 3,347 | 3,068  | 2,832   | 2,630   |
|                  |                      |                           | D | 0.030            | 0.048 | 0.069 | 0.093 | 0.122 | 0.154 | 0.190 | 0.230 | 0.274  | 0.322   | 0.373   |
| 2-1/2 x 3/16     | 28.6                 | 10'-8"                    | U | 11,364           | 7,273 | 5,051 | 3,711 | 2,841 | 2,245 | 1,818 | 1,503 | 1,263  | 1,076   | 928   |
|                  |                      |                           | D | 0.034            | 0.054 | 0.077 | 0.105 | 0.137 | 0.174 | 0.214 | 0.259 | 0.309  | 0.362   | 0.420   |
|                  |                      |                           | C | 11,364           | 9,091 | 7,576 | 6,494 | 5,682 | 5,051 | 4,545 | 4,132 | 3,788  | 3,497   | 3,247   |
|                  |                      |                           | D | 0.027            | 0.043 | 0.062 | 0.084 | 0.110 | 0.139 | 0.171 | 0.207 | 0.247  | 0.290   | 0.336   |

\* Weight per square foot based upon IGtrū™ 11-W-4 grating. Add .60 psf for 2" on center cross bars.

\*\* Maximum pedestrian load is defined as a 100# Uniform Load with deflection  $\leq 1/4$  inch.

The 1/4" maximum deflection criteria is considered consistent with pedestrian comfort, but may be exceeded for other loading conditions at the discretion of the specifying authority.

Note: When gratings with serrated surface are specified, the depth of the grating required for a specific load will be 1/4" greater than that shown in these tables.

### Panel Widths

Grating panels are available from stock in nominal 24" and 36" widths (24" max for type "WS"). When considering alternative widths, consult this table to select widths that will maintain uniform "out-to-out" spacing of the bearing bars. Specified widths deviating from this table will be fabricated to size with side banding and the bar spacing on one side of the finished panel will deviate from the spacing throughout the remainder of the panel.

| Number of Bearing Bars<br>Panel Width | 2<br>7/8"       | 3<br>1-1/2"    | 4<br>2-3/16"    | 5<br>2-13/16"   | 6<br>3-1/2"    | 7<br>4-1/8"     | 8<br>4-13/16"  | 9<br>5-7/16"   | 10<br>6-1/8"    | 11<br>6-3/4"   | 12<br>7-7/16" | 13<br>8-1/16"   | 14<br>8-3/4"   | 15<br>9-3/8"   | 16<br>10-1/16" |
|---------------------------------------|-----------------|----------------|-----------------|-----------------|----------------|-----------------|----------------|----------------|-----------------|----------------|---------------|-----------------|----------------|----------------|----------------|
| Number of Bearing Bars<br>Panel Width | 17<br>10-11/16" | 18<br>11-3/8"  | 19<br>12"       | 20<br>12-11/16" | 21<br>13-5/16" | 22<br>14"       | 23<br>14-5/8"  | 24<br>15-5/16" | 25<br>15-15/16" | 26<br>16-5/8"  | 27<br>17-1/4" | 28<br>17-15/16" | 29<br>18-9/16" | 30<br>19-1/4"  | 31<br>19-7/8"  |
| Number of Bearing Bars<br>Panel Width | 32<br>20-9/16"  | 33<br>21-3/16" | 34<br>21-7/8"   | 35<br>22-1/2"   | 36<br>23-3/16" | 37<br>23-13/16" | 38<br>24-1/2"  | 39<br>25-1/8"  | 40<br>25-13/16" | 41<br>26-7/16" | 42<br>27-1/8" | 43<br>27-3/4"   | 44<br>28-7/16" | 45<br>29-1/16" | 46<br>29-3/4"  |
| Number of Bearing Bars<br>Panel Width | 47<br>30-3/8"   | 48<br>31-1/16" | 49<br>31-11/16" | 50<br>32-3/8"   | 51<br>33"      | 52<br>33-11/16" | 53<br>34-5/16" | 54<br>35"      | 55<br>35-5/8"   | 56<br>36-5/16" |               |                 |                |                |                |

Panel widths indicated are for gratings with 3/16" thick bearing bars. For 1/8" thick bearing bars deduct 1/16" from the stated values.

Indicates stock panel widths for type "DTS". Indicates stock panel widths for type "WS" (24" max).