

Steel Bar Grating

15 Space Load Table

Use this table when evaluating spans and loads for the following types of steel grating:
15-W-4, 15-W-2, 15-DT-4, 15-DT-2, 15-SL-4 and 15-SL-2

Bearing Bar Size	Approx. Weight psf *	Maximum Pedestrian Span**		Unsupported Span																	
				2'-0"	2'-6"	3'-0"	3'-6"	4'-0"	4'-6"	5'-0"	5'-6"	6'-0"	6'-6"	7'-0"	8'-0"	9'-0"					
3/4 x 3/16	6.9	4'-0"	U D C D	675 0.099 675 0.079	432 0.155 540 0.124	300 0.223 450 0.179	220 0.304 386 0.243	169 0.397 338 0.318	133 0.503 300 0.402	108 0.621 270 0.497	All loads and deflections are theoretical and based upon the gross sections of the bearing bars, using a fiber stress of 18,000 psi.										
1 x 1/8	6.2	4'-6"	U D C D	800 0.074 800 0.060	512 0.116 640 0.083	356 0.168 533 0.134	261 0.228 457 0.182	200 0.298 400 0.238	158 0.377 356 0.302	128 0.466 320 0.372	The values are not intended to be absolute since the actual load capacity will be affected by the slight variations in mill and manufacturing tolerances.										
1 x 3/16	8.9	5'-0"	U D C D	1,200 0.074 1,200 0.060	768 0.116 960 0.093	533 0.168 800 0.134	392 0.228 686 0.182	300 0.298 600 0.238	237 0.377 533 0.302	192 0.466 480 0.372	159 0.563 436 0.451	133 0.670 400 0.536	U = Safe Uniform Load in pounds/sq. ft. C = Concentrated Load in pounds/ft. of grating width D = Deflection in inches								
1-1/4 x 1/8	7.5	5'-4"	U D C D	1,250 0.060 1,250 0.048	800 0.093 1,000 0.074	556 0.134 833 0.107	408 0.182 714 0.146	313 0.238 625 0.191	247 0.302 556 0.241	200 0.372 500 0.298	165 0.451 455 0.360	139 0.536 417 0.429	118 0.629 385 0.504								
1-1/4 x 3/16	11.0	5'-11"	U D C D	1,875 0.060 1,875 0.048	1,200 0.093 1,500 0.074	833 0.134 1,250 0.107	612 0.182 1,071 0.146	469 0.238 938 0.191	370 0.302 833 0.241	300 0.372 750 0.298	248 0.451 682 0.360	208 0.536 625 0.429	178 0.629 577 0.504	153 0.730 536 0.584							
1-1/2 x 1/8	8.9	6'-2"	U D C D	1,800 0.050 1,800 0.040	1,152 0.078 1,440 0.062	800 0.112 1,200 0.089	588 0.152 1,029 0.122	450 0.199 900 0.159	356 0.251 800 0.201	288 0.310 720 0.248	238 0.376 655 0.300	200 0.447 600 0.358	170 0.524 554 0.420	147 0.608 514 0.487	113 0.794 450 0.636						
1-1/2 x 3/16	13.2	6'-10"	U D C D	2,700 0.050 2,700 0.040	1,728 0.078 2,160 0.062	1,200 0.112 1,800 0.089	882 0.152 1,543 0.122	675 0.199 1,350 0.159	533 0.251 1,200 0.201	432 0.310 1,080 0.248	357 0.376 982 0.300	300 0.447 900 0.358	256 0.524 831 0.420	220 0.608 771 0.487	169 0.794 675 0.636	133 1.006 600 0.804					
1-3/4 x 1/8	10.4	6'-11"	U D C D	2,450 0.043 2,450 0.034	1,568 0.067 1,980 0.053	1,089 0.096 1,833 0.077	800 0.130 1,400 0.104	613 0.170 1,225 0.136	484 0.215 1,089 0.172	392 0.266 980 0.213	324 0.322 891 0.257	272 0.383 817 0.306	232 0.450 754 0.360	200 0.521 700 0.487	153 0.681 613 0.545	121 0.862 544 0.689					
1-3/4 x 3/16	15.3	7'-8"	U D C D	3,675 0.043 3,675 0.034	2,352 0.067 2,940 0.053	1,633 0.096 2,450 0.077	1,200 0.130 2,100 0.104	919 0.170 1,838 0.136	726 0.215 1,633 0.172	588 0.266 1,470 0.213	486 0.322 1,470 0.257	408 0.393 1,225 0.306	348 0.450 1,131 0.360	300 0.521 1,050 0.471	230 0.681 919 0.545	182 0.862 817 0.689					
2 x 1/8	11.8	7'-7"	U D C D	3,200 0.037 3,200 0.030	2,048 0.058 2,560 0.047	1,422 0.084 2,133 0.067	1,045 0.114 1,829 0.091	800 0.149 1,600 0.119	632 0.189 1,422 0.151	512 0.233 1,280 0.186	423 0.282 1,164 0.225	356 0.335 1,067 0.268	303 0.393 985 0.315	261 0.456 914 0.365	200 0.596 800 0.477	158 0.754 711 0.603					
2 x 3/16	17.3	8'-6"	U D C D	4,800 0.037 4,800 0.030	3,072 0.058 3,840 0.047	2,133 0.084 3,200 0.067	1,567 0.114 2,743 0.091	1,200 0.149 2,400 0.119	948 0.189 2,133 0.151	768 0.233 1,920 0.186	635 0.282 1,746 0.225	533 0.335 1,600 0.268	454 0.393 1,477 0.315	392 0.456 1,371 0.365	300 0.596 1,200 0.477	237 0.754 1,067 0.603					
2-1/4 x 3/16	19.4	9'-3"	U D C D	6,075 0.033 6,075 0.026	3,888 0.052 4,860 0.041	2,700 0.074 4,050 0.060	1,984 0.101 3,471 0.081	1,519 0.132 3,038 0.106	1,200 0.168 2,700 0.134	972 0.207 2,430 0.166	803 0.250 2,430 0.200	675 0.298 2,209 0.238	575 0.350 2,025 0.238	496 0.406 1,869 0.280	380 0.530 1,736 0.324	300 0.670 1,519 0.424					
2-1/2 x 3/16	21.5	10'-0"	U D C D	7,500 0.030 7,500 0.024	4,800 0.047 6,000 0.037	3,333 0.067 5,000 0.054	2,449 0.091 4,286 0.073	1,875 0.151 3,750 0.095	1,482 0.151 3,333 0.121	1,200 0.186 3,000 0.149	992 0.225 2,727 0.180	833 0.268 2,500 0.215	710 0.315 2,308 0.215	612 0.365 2,143 0.292	469 0.477 1,875 0.381	370 0.603 1,667 0.483					

* Weight per square foot based upon 15-W-4 grating. Add .60 psf for 2" on center cross bars.

** Maximum pedestrian load is defined as a 100# Uniform Load with deflection $\leq 1/4$ inch.

The 1/4" maximum deflection criteria is considered consistent with pedestrian comfort, but may be exceeded for other loading conditions at the discretion of the specifying authority.

Note: When gratings with serrated surface are specified, the depth of the grating required for a specific load will be 1/4" greater than that shown in these tables.

Panel Widths

Grating panels are available from stock in nominal 24" and 36" widths. When considering alternative widths, consult this table to select widths that will maintain uniform "out-to-out" spacing of the bearing bars. Specified widths deviating from this table will be fabricated to size with side banding and the bar spacing on one side of the finished panel will deviate from the spacing throughout the remainder of the panel.

No. of Bearing Bars Panel Width	2 1-1/8"	3 2-1/16"	4 3"	5 3-15/16"	6 4-7/8"	7 5-13/16"	8 6-3/4"	9 7-11/16"	10 8-5/8"	11 9-9/16"	12 10-1/2"	13 11-7/16"	14 12-3/8"	15 13-5/16"	16 14-1/4"	
No. of Bearing Bars Panel Width	17 15-3/16"	18 16-1/8"	19 17-1/16"	20 18"	21 18-15/16"	22 19-7/8"	23 20-13/16"	24 21-3/4"	25 22-11/16"	26 23-5/8"	27 24-9/16"	28 25-1/2"	29 26-7/16"	30 27-3/8"	31 28-5/16"	
No. of Bearing Bars Panel Width	32 29-1/4"	33 30-3/16"	34 31-1/8"	35 32-1/16"	36 33"	37 33-15/16"	38 34-7/8"	39 35-13/16"								

Panel widths indicated are for gratings with 3/16" thick bearing bars. For 1/8" thick bearing bars deduct 1/16" from the stated values.

■ Indicates stock panel widths.